

# **Certificate of Compliance**

**Certificate:** 1136976 (112526)

**Project:** 2341108

Issued to: M.B. Sturgis Inc.

555 Fee Fee Rd St. Louis, MO 63043-3256 USA Attention: Brian Diel Master Contract: 162505

Date Issued:

October 18, 2010

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.



James A. Doherty

Issued by: James A. Doherty

### PRODUCTS

CLASS 3312 01	- GAS CONVENIENCE OUTLETS AND ENCLOSURES
CLASS 3312 81	- GAS CONVENIENCE OUTLETS AND ENCLOSURES - Certified to
	U.S. Standards
CLASS 3305 87	- GAS ACCESSORY DEVICES - Quick Disconnect-Certified to U.S.
	Standards
CLASS 3305 07	- GAS ACCESSORY DEVICES - Ouick Disconnect

#### CLASS 3312 01 - GAS CONVENIENCE OUTLETS AND ENCLOSURES

CLASS 3312 81 - GAS CONVENIENCE OUTLETS AND ENCLOSURES-Certified to U.S. Standards

# Trade Name: COUPLE-SAFE

#### For Indoor/Outdoor Use (-40°F to 200°F)

Model Number:	Rated Pressure:	Inlet (inch):	Outlet (inch):
4/BV500C	5 PSI	$\frac{1}{2}$ NPT(F)	$\frac{1}{2}$ NPT(F)
5/BV750C	5 PSI	<sup>3</sup> / <sub>4</sub> NPT(F)	<sup>3</sup> / <sub>4</sub> NPT(F)



**Certificate:** 1136976 (112526)

**Project:** 2341108

Master Contract:162505Date Issued:October 18, 2010

CLASS 3305 07 - ACCESSORY DEVICES (GAS) Quick Disconnect

CLASS 3305 87 - ACCESSORY DEVICES (GAS) Quick Disconnect-Certified to U.S. Standards

**Trade Name: COUPLE-SAFE** 

For Indoor/Outdoor Use (-40°F)

Model Number:	Rated Pressure:	Inlet (inch):	Outlet (inch):
4-F8	1/2 PSI	$\frac{1}{2}$ NPT(F)	$\frac{1}{2}$ NPT(F)
5-F12	1/2 PSI	<sup>3</sup> / <sub>4</sub> NPT(F)	<sup>3</sup> / <sub>4</sub> NPT(F)

## **APPLICABLE REQUIREMENTS**

ANSI Z21.90-2001 • CSA 6.24-2001 Gas Convenience Outlets

ANSI Z21.41-2003•CSA 6.9-2003 Quick Disconnect Device Devices For Use With Gas Fuel Appliances

ANSI Z21.41a-2005•CSA 6.9b-2005 Addenda

ANSI Z21.41b-2010•CSA 6.9b-2010 Addenda